



LEENDERS

SINCE 1979

LYNNE

DATASHEET

EN

NL

DE

FR

TECHNICAL DOCUMENTATION FOR SOLID FUEL LOCAL SPACE HEATERS

Manufacturer	Harrie Leenders Haardkachels B.V., Industrierweg 25, 5688 DP Oirschot, The Netherlands	General description	Freestanding solid fuel local space heater without hot water supply
Model identifier	LYNNE	Specific precautions for assembly, intallation or maintenance	Precautions for assembly, installation and maintenance are described in: - Installation instructions - Instructions for use & maintenance
Equivalent models	SORENNE	Calculations	$EEI = (\mu S_{on} \cdot BLF) - 10\% + F(2) + F(3) - F(4) - F(5)$ $\mu S_{on} = \mu_{th,nom}$ $\eta_s = \eta_{nom} - 10\% + F(2) + F(3) - F(4) - F(5)$
Test report nr.	1639-AoP-EZKA/2025-11/006-1	Testing conditions	Tested according: EN16510-2-1:2022
Harmonized European standard	EN16510-2-1:2022		
Indirect heating function	No		
Direct heat output (kW)	7,4		
Indirect heat output (kW)	-		

Fuel	Preferred fuel (only one)	Other suitable fuel(s)	Emissions at nominal heat output [mg/Nm³ (13 % O²)]				Emissions at minimum heat output [mg/Nm³ (13 % O²)]			
			PM	OGC	CO	NOx	PM	OGC	CO	NOx
Wood logs, moisture content < 25 %	Yes	No	38	46	584	117	N/A	N/A	N/A	N/A
Compressed wood, moisture content < 12 %	No	Yes	38	46	584	117	N/A	N/A	N/A	N/A
Other woody biomass	No	No								
Non-woody biomass	No	No								
Anthracite and dry steam coal	No	No								
Hard coke	No	No								
Low temperature coke	No	No								
Bituminous coal	No	No								
Lignite briquettes	No	No								
Peat briquettes	No	No								
Blended fossil fuel briquettes	No	No								
Other fossil fuel	No	No								
Blended biomass and fossil fuel briquettes	No	No								
Other blend of biomass and solid fuel	No	No								

Characteristics when operating with the preferred fuel

Seasonal space heating efficiency η_s [%]	74,6
Energy efficiency index (EEI)	102,9

	Symbol	Value	Unit	Type of heat output/room temperature control (select one)	
Heat output					
Nominal heat output	P_{nom}	7,4	kW	Single-stage heat output, no room temperature control	No
Minimum heat output (indicative)	P_{min}	N/A	kW	Two or more manual stages, no room temperature control	Yes
Useful efficiency (NCV as received)				With mechanic thermostat room temperature control	No
Useful efficiency at nominal heat output	$\eta_{th,nom}$	76,7	%	With electronic room temperature control	No
Useful efficiency at minimum heat output (indicative)	$\eta_{th,min}$	N/A	%	With electronic room temperature control plus day timer	No
Auxilliary power consumption				With electronic room temperature control plus week timer	No
At nominal heat output	e_{lmax}	N/A	kW		
At minimum heat output	e_{lmin}	N/A	kW	Other control options (multiple selection possible)	
In standby mode	e_{lSB}	N/A	kW	Room temperature control, with presence detection	No
Permanent pilot flame power requirement				Room temperature control, with open window detection	No
Pilot flame power requirement (if applicable)	P_{pilot}	N/A	kW	With distance control option	No



Power range: min./ max per hour [1]	2.5-9 kWh
Vermogensbereik; min./max. per uur	
Leistungsbereich; min.max. pro Stunde	
Plage d'utilisation, puissance min./max. par heure	
Fuel requirement per hour, min./max. [2]	0.7- 3 kg
Navul hoeveelheid per uur, min./max.	
Holzaufgabemenge pro Stune, min./max.	
Charge de bois par heure, min./max.	
Weight	125 Kg
Gewicht	
Gewicht	
Poids	
Efficiency	77.2 %
Rendement	
Wirkungsgrad	
Rendement	
Energy Efficiency Class	A
Energie Efficiëntie Klasse	
Energie Effizienz Klasse	
Classe d'efficacité énergétique	
Energy Efficiency Index	102,9
Energie Efficiëntie Index	
Energie Effizienz Index	
Index d'efficacité énergétique	
Dust	38 mg/Nm3
Stof	
Staub	
Poussieres fines	
CO	0.05 %
Information for chimney calculation	7.4 kWh
Informatie voor schoorsteenberekening	7.9 g/s
Information für den Schornsteinfegermeister	284 °C
Information pour le calcul de conduit et de tirage de cheminée	0.05% CO
	0.115 mbar
EN 13240	1639-AoP-EZKA/2025-11/006-1
Art.15a B-VG	☒
VKF	☒
BlmschV. Stufe 2	☒
Flamme Rucola	☒
Smoke Control	☒

[1]

The minimum power is required to keep the stove at operating temperature.

Het minimale vermogen is nodig om de haard op bedrijfstemperatuur te houden.

Die minimale Leistung ist notwendig, damit die Betriebstemperatur des Kaminofens aufrechterhalten bleibt.

Une puissance minimum est nécessaire pour maintenir le poêle à une bonne température de fonctionnement.

[2]

At 80% efficiency, 1kg of wood with 15% rest moist, gives of approx. 3,5kW energy.

Bij een rendement van 80%, geeft 1kg stookhout met 15% restvocht, ongeveer 3,5kW energie.


Bei einem Wirkungsgrad von 80%, ergibt 1 kg Holz mit 15% Restfeuchtigkeit etwa 3,5kW Energie.

Avec un rendement de 80%, 1kg de bois avec un taux d'humidité de 15% délivre environ 3,5 kW de énergie.



Color variations mantle	black/antracite
Kleurvariaties mantel	zwart/antraciet
Farbvariationen Mantel	schwarz/anthrazit
Les variations de couleur manteau	noir/anthracite
Color sole & top plate	black/antracite
Kleur voet & bovenplaat	zwart/antraciet
Farb Fuß & obere Platte	schwarz/anthrazit
Couleur pied & plateau dessus	noir/anthracite
Flue Diameter	Ø150 mm
Diameter afvoer	
Anschlussdurchmesser	
Diamètre de conduit	
Rotatable top flue	2 x 45 °
Draaibaar bovenafvoer	
Drehbar mit Anschluss oben	
Sortie dessus pivotable	
Optional Plus heat storage	-
Optionele Plus stenen set	
Optional Plus Speicherset	
Ceramiques d'accumultion optional	
Fresh air supply	in base: to wall
Verse luchtvoorziening	in voet: naar wand
Frischlufzufuhr	im Fuß: zur Wand
Prise d'air	dans le pied: par le mur
Possibility to level foot	☒
Voet waterpas te stellen	
Fuss mit Wasserwaage ausrichten	
Mise à niveau du pied	

Fresh air supply/verse luchtvoorziening/Frischlufzufuhr/prise d' air





flammable
brandbaar
brennbar
inflammable






Appliance must be placed on a non-combustible wall.


Toestel moet aan een onbrandbare wand bevestigd worden.

Das Gerät muss an einer unbrennbare Wand befestigt werden.

L'appareil doit être fixé contre un support inflammable.

nonflammable
onbrandbaar
nicht brennbar
inflammable





Toleranties tenzij anders vermeld: ± 1° ± 10,5 mm		Afwerkingsgraad oppervlaktes HLH 1/3 nom		Afwerkingsgraad oppervlaktes tenzij anders vermeld: HLH 1/3 nom		Project Lynne		Assembly no.	
A3		Units MM		Proj. H4		Titel Lynne			